


# RONDELLE ELASTICHE A SPIRALE (GROWER) HELICAL SPRING WASHERS (GROWER)



DISPONIBILI: Brunito - Zincato bianco o Zincato Giallo deidrogenato secondo RoHS

Also treatments à richiesta

AVAILABLE: Black - White zinc plated or Yellow zinc plated with dehydrogenation according to RoHS - Other coatings on request

	<b>ISO</b>	<b>UNI</b>	<b>DIN</b>
	-	<b>1751</b>	<b>127B</b>
MATERIALE MATERIAL	ACCIAIO PER MOLLE SPRING STEEL		
PROPRIETÀ MECCANICHE MECHANICAL PROPERTIES	SECONDO ACCORDING TO		UNI EN 10270
DUREZZA HARDNESS	<b>430-530 HV</b>		
TOLLERANZE TOLERANCES	SECONDO ACCORDING TO		DIN 127

<b>d</b>	<b>d<sub>1</sub></b>	<b>d<sub>2</sub></b>	<b>h min</b>	<b>s</b>	<b>Kg</b>
M 2	2,2	4	1	0,5	0,033
M 2,5	2,5	4,5	1,2	0,6	0,053
M 3	3,2	5,8	1,6	0,8	0,112
M 4	4,3	7,3	1,8	0,9	0,18
M 5	5,3	8,9	2,4	1,2	0,36
M 6	6,4	11,4	3,2	1,6	0,83
M 7	7,1	12,8	3,2	1,6	0,93
M 8	8,4	14,4	4	2	1,60
M 10	10,5	17,5	4,4	2,2	2,53
M 12	13	21	5	2,5	3,82
M 14	15	24	6	3	6,01
M 16	17	27	7	3,5	8,91
M 18	19	29	7	3,5	9,73
M 20	21	33	8	4	15,2
M 22	23	35	8	4	16,5
M 24	25	39	10	5	26,2
M 27	28	42	10	5	28,7
M 30	31	47	12	6	44,3
M 33	34	54	12	6	63,0
M 36	37	57	12	6	67,3
M 39	40	61	12	6	71,7
M 42	43	67	14	7	111
M45	46	70	14	7	117

PESO PER 1000 PEZZI / WEIGHT FOR 1000 PCS